

GVTV.R38152 - FIRE DOOR AND FIRE WINDOW FRAMES

Fire Door and Fire Window Frames

See General Information for Fire Door and Fire Window Frames

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38152

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10C:

Three sided steel frame with or without transoms (single swing or pair).

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10B (neutral pressure):

Three sided frames with or without transom (single swing or pair).

Trademark and/or Tradename: "SFFECO",



Last Updated on 2018-08-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV.R38152 - FIRE DOOR AND FIRE WINDOW FRAMES

Fire Door and Fire Window Frames

See General Information for Fire Door and Fire Window Frames

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38152

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10C:

Three sided steel frame with or without transoms (single swing or pair).

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10B (neutral pressure):

Three sided frames with or without transom (single swing or pair).

Trademark and/or Tradename: "SFFECO",



Last Updated on 2018-08-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV.R22310 - FIRE DOOR AND FIRE WINDOW FRAMES

Fire Door and Fire Window Frames

See General Information for Fire Door and Fire Window Frames

SAUDI FACTORY FOR FIRE EQUIPMENT CO

R22310

2ND INDUSTRIAL AREA

AL-KHARJ RD

PO BOX 58469

RIYADH, 11515 SAUDI ARABIA

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10C:

Three sided steel frame with or without transoms (single swing or pair).

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10B (neutral pressure):

Three sided frames with or without transom (single swing or pair).

Last Updated on 2007-01-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV.R22310 - FIRE DOOR AND FIRE WINDOW FRAMES

Fire Door and Fire Window Frames

See General Information for Fire Door and Fire Window Frames

SAUDI FACTORY FOR FIRE EQUIPMENT CO

R22310

2ND INDUSTRIAL AREA

AL-KHARJ RD

PO BOX 58469

RIYADH, 11515 SAUDI ARABIA

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10C:

Three sided steel frame with or without transoms (single swing or pair).

Door Frames for use as a component in fire door assemblies that meet the requirements of UL10B (neutral pressure):

Three sided frames with or without transom (single swing or pair).

Last Updated on 2007-01-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV7.R38152 - FIRE DOOR AND FIRE WINDOW FRAMES CERTIFIED FOR CANADA

Fire Door and Fire Window Frames Certified for Canada

See General Information for Fire Door and Fire Window Frames Certified for Canada

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38152

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Door frames: Welded three sided single frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 1200 mm in width and 2261 mm in height.

Door frames: Welded three sided pair type frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 2313 mm in width and 2269 mm in height.

Trademark and/or Tradename: "SFFECO",



Last Updated on 2018-08-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV7.R38152 - FIRE DOOR AND FIRE WINDOW FRAMES CERTIFIED FOR CANADA

Fire Door and Fire Window Frames Certified for Canada

See General Information for Fire Door and Fire Window Frames Certified for Canada

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38152

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Door frames: Welded three sided single frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 1200 mm in width and 2261 mm in height.

Door frames: Welded three sided pair type frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 2313 mm in width and 2269 mm in height.

Trademark and/or Tradename: "SFFECO",



Last Updated on 2018-08-20

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV7.R22310 - FIRE DOOR AND FIRE WINDOW FRAMES CERTIFIED FOR CANADA

Fire Door and Fire Window Frames Certified for Canada

See General Information for Fire Door and Fire Window Frames Certified for Canada

SAUDI FACTORY FOR FIRE EQUIPMENT CO

R22310

2ND INDUSTRIAL AREA

AL-KHARJ RD

PO BOX 58469

RIYADH, 11515 SAUDI ARABIA

Door frames: Welded three sided single frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 1200 mm in width and 2261 mm in height.

Door frames: Welded three sided pair type frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 2313 mm in width and 2269 mm in height.

Last Updated on 2007-01-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GVTV7.R22310 - FIRE DOOR AND FIRE WINDOW FRAMES CERTIFIED FOR CANADA

Fire Door and Fire Window Frames Certified for Canada

See General Information for Fire Door and Fire Window Frames Certified for Canada

SAUDI FACTORY FOR FIRE EQUIPMENT CO

R22310

2ND INDUSTRIAL AREA

AL-KHARJ RD

PO BOX 58469

RIYADH, 11515 SAUDI ARABIA

Door frames: Welded three sided single frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 1200 mm in width and 2261 mm in height.

Door frames: Welded three sided pair type frames for use in 3/4, 1-1/2, 3 hr locations. Maximum size of frame: 2313 mm in width and 2269 mm in height.

Last Updated on 2007-01-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSNVC.R38151 - FIRE DOORS

Fire Doors

See General Information for Fire Doors

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO
S-10833
JEBEL ALI FREE ZONE
AUTHORITY SOUTH 1
DUBAI, 261281 UNITED ARAB EMIRATES
Vertically Stiffened Hollow-Metal Doors: For installation in 3 h locations. Maximum Size of Opening.

R38151

Type of Door	Opening Size, mm	
	Width	Height
Single swinging	1100	2200

Last Updated on 2015-06-04

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSNVC.R22331 - FIRE DOORS

Fire Doors

See General Information for Fire Doors

SAUDI FACTORY FOR FIRE EQUIPMENT CO

R22331

2ND INDUSTRIAL AREA

AL-KHARJ RD

PO BOX 58469

RIYADH, 11515 SAUDI ARABIA

Vertically Stiffened Hollow-Metal Doors: For installation in 3 h locations. Maximum Size of Opening.

Type of Door	Opening Size, mm	
	Width	Height
Single swinging	1100	2200

Last Updated on 2005-09-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSYX.R38151 - SWINGING-TYPE FIRE DOORS

Swinging-type Fire Doors

See General Information for Swinging-type Fire Doors

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38151

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Swinging doors may be provided as follows:

Max Rating	Opening Type	Hollow Metal Type Door	Steel Covered Composite Type Door
2 Hr	SSingle or Pair With Astragal	X	—
	Single Point Lock/Flush Bolts		
	Single Rim/Mortise Fire Exit Hardware		
	Door with Automatic Louver		
	Max 100 sq in. Glazing		
2 Hr	Pair With Astragal	—	X
	Single Point Lock/Flush Bolts		
3 Hr	Single		
	Single Point Lock/Flush Bolts Rim/Mortise/Fire Exit Hardware	—	X
3Hr	Single or Pair With Astragal	X	—
	Single Point Lock/Flush Bolts		
	Single Rim/Mortise Fire Exit Hardware		
3 Hr	Single	X	—
	Single Point Lock/Flush Bolts Rim/Mortise/Fire Exit Hardware		
	450°F Temperature Rise	X	—
1 Hr	Single or Pair With Astragal		
	Single Point Lock/Flush Bolts		
	Single Rim/Mortise Fire Exit Hardware		
	450°F Temperature Rise		

Trademark and/or Tradename:  , "SFFECO"

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSYX7.R22331 - SWINGING-TYPE FIRE DOORS CERTIFIED FOR CANADA

Swinging-type Fire Doors Certified for Canada

See General Information for Swinging-type Fire Doors Certified for Canada

SAUDI FACTORY FOR FIRE EQUIPMENT CO

R22331

2ND INDUSTRIAL AREA

AL-KHARJ RD

PO BOX 58469

RIYADH, 11515 SAUDI ARABIA

Swinging doors may be provided as follows:

Max Rating	Door Type	Steel Stiffened	Steel Covered			Honeycomb Sheet Metal
			Mineral Core Composite	Hollow Metal	Honeycomb Metal	
3 Hr	Single with Single Point Lock/Rim, Mortise Fire Exit Hardware 450°F Temperature Rise	X	—	—	—	—
1 Hr	Single with Single Point Lock / Rim, Mortise Fire Exit Hardware 450 F (218 C) Temp Rise DoorPair with Astragal Single Point Lock, Mortise Fire Exit Hardware, Flush Bolts / Vertical Rod Fire Exit Hardware 450 F temp Rise Door	X	—	—	—	—

Last Updated on 2007-01-19

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSYX7.R38151 - SWINGING-TYPE FIRE DOORS CERTIFIED FOR CANADA

Swinging-type Fire Doors Certified for Canada

See General Information for Swinging-type Fire Doors Certified for Canada

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38151

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Swinging doors may be provided as follows:

Max Rating	Opening Type	Hollow Metal Type Door	Steel Covered Composite Type Door
2 Hr	SSingle or Pair With Astragal	X	—
	Single Point Lock/Flush Bolts		
	Single Rim/Mortise Fire Exit Hardware		
	Door with Automatic Louver		
	Max 100 sq in. Glazing		
2 Hr	Pair With Astragal	—	X
	Single Point Lock/Flush Bolts		
3 Hr	Single		
	Single Point Lock/Flush Bolts Rim/Mortise/Fire Exit Hardware	—	X
3Hr	Single or Pair With Astragal	X	—
	Single Point Lock/Flush Bolts		
	Single Rim/Mortise Fire Exit Hardware		
3 Hr	Single	X	—
	Single Point Lock/Flush Bolts Rim/Mortise/Fire Exit Hardware		
	450°F Temperature Rise	X	—
1 Hr	Single or Pair With Astragal		
	Single Point Lock/Flush Bolts		
	Single Rim/Mortise Fire Exit Hardware		
	450°F Temperature Rise		

Trademark and/or Tradename:  , "SFFECO"

The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSZN.R22331 - SWINGING-TYPE FIRE DOORS, POSITIVE-PRESSURE TESTED

Swinging-type Fire Doors, Positive-pressure Tested

See General Information for Swinging-type Fire Doors, Positive-pressure Tested

SAUDI FACTORY FOR FIRE EQUIPMENT CO
2ND INDUSTRIAL AREA
AL-KHARJ RD
PO BOX 58469
RIYADH, 11515 SAUDI ARABIA
Swinging doors may be provided as follows:

R22331

Max.		Door	Opening	Min Size ft- in(mm)		Max Size ft-in(mm)		Latching		Temp Rise Rating		Smoke
Model	Rating	Type	Type	Category	W	H	W	H	Hardware	Accessories [*]	°F(°C)	Control
-	3 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Cylindrical, Mortise	Fire Door Viewer, Glazing, Louver	450 (250)	S
	3 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Mortise Fire Exit, Rim Exit	Fire Door Viewer, Glazing	450 (250)	S
-	1 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Cylindrical, Mortise	Fire Door Viewer, Glazing, Louver	450 (250)	S
	1 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Mortise Fire Exit, Rim Exit	Fire Door Viewer, Glazing	450 (250)	S
	1 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Cylindrical, Mortise	Fire Door Viewer, Glazing, Louver	450 (250)	S


2/4/2019

SWINGING-TYPE FIRE DOORS, POSITIVE-PRESSURE TESTED | UL Product iQ

	1 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Concealed Vertical Rod Exit, Mortise Fire Exit, Surface Vertical Rod Exit	Fire Door Viewer, Glazing	450 (250)	S
--	--------	-----------------------------------	---------------------	---	---	---	-----------------	-----------------	--	---------------------------------	--------------	---

[*] - Additional information regarding accessories can be found under the Guide Card GSZN

Last Updated on 2017-02-25



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"

GSZN.R38151 - SWINGING-TYPE FIRE DOORS, POSITIVE-PRESSURE TESTED

Swinging-type Fire Doors, Positive-pressure Tested

See General Information for Swinging-type Fire Doors, Positive-pressure Tested

SAUDI FACTORY FOR FIRE EQUIPMENT FZCO

R38151

S-10833

JEBEL ALI FREE ZONE

AUTHORITY SOUTH 1

DUBAI, UNITED ARAB EMIRATES

Swinging doors may be provided as follows:


Model	Rating	Door Type	Opening Type	Category	Min Size ft-in(mm)		Max Size ft-in(mm)		Latching Hardware	Ac
					W	H	W	H		
-	3 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Cylindrical, Mortise	
	3 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Mortise Fire Exit, Rim Exit	
-	1 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Cylindrical, Mortise	
	1 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Mortise Fire Exit, Rim Exit	
-	1 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Cylindrical, Mortise	

	1 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Mortise Fire Exit, Surface Vertical Rod Exit	
-	2 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Cylindrical, Mortise	I
	2 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	3 - 7 (1092)	7 - 3 (2210)	Concealed Vertical Rod Exit, Mortise Fire Exit, Rim Exit, Surface Vertical Rod Exit	I
-	2 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Cylindrical, Mortise	I
	2 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Concealed Vertical Rod Exit, Mortise Fire Exit, Rim Exit, Surface Vertical Rod Exit	I
-	3 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	4 - 0.25 (1226)	8 - 0.4500000000000003 (2450)	Cylindrical, Mortise	(C

	2 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 2.78 (2204)	7 - 2.63 (2200)	Concealed Vertical Rod Exit, Mortise, Mortise Fire Exit, Rim Exit, Surface Vertical Rod Exit	(C) (C) Co
-	2 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Cylindrical, Mortise	I
	2 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	7 - 3 (2210)	7 - 3 (2210)	Concealed Vertical Rod Exit, Mortise Fire Exit, Rim Exit, Surface Vertical Rod Exit	I
-	3 hour	Hollow-Metal (Steel Stiffened)	Pair w/ Astragal	A	-	-	9 - 6.099999999999999 (2898)	9 - 8.099999999999999 (2949)	Electrically-controlled Single-point, Mortise, Mortise Fire Exit, Mortise w/ Auxiliary Locks, Rim Exit	(C) (C) Co
	3 hour	Hollow-Metal (Steel Stiffened)	Single	A	-	-	4 - 0.25 (1226)	9 - 8.099999999999999 (2949)	Cylindrical, Mortise, Mortise Fire Exit, Mortise w/ Auxiliary Locks, Rim Exit	(C) (C)

[*] - Additional information regarding accessories can be found under the Guide Card GSZN

Trademark and/or Tradename: "SFFECO" , 



The appearance of a company's name or product in this database does not in itself assure that products so identified have been manufactured under UL's Follow-Up Service. Only those products bearing the UL Mark should be considered to be Certified and covered under UL's Follow-Up Service. Always look for the Mark on the product.

UL permits the reproduction of the material contained in the Online Certification Directory subject to the following conditions: 1. The Guide Information, Assemblies, Constructions, Designs, Systems, and/or Certifications (files) must be presented in their entirety and in a non-misleading manner, without any manipulation of the data (or drawings). 2. The statement "Reprinted from the Online Certifications Directory with permission from UL" must appear adjacent to the extracted material. In addition, the reprinted material must include a copyright notice in the following format: "© 2019 UL LLC"